



FLEXIBLE SANDING BOARDS

FSB 042071
FSB 056111
FSB 084112
FSB 112113
FSB 196114



TECHNICAL PARAMETERS

model	FSB 042071	FSB 056111	FSB 084112	FSB 112113	FSB 196114
dimensions of the plate	420 x 70 mm	560 x 115 mm	840 x 115 mm	1120 x 90 mm	1960 x 115 mm
min. convex radius	350 mm	500 mm	800 mm	1200 mm	2100 mm
min. concave radius	350 mm	600 mm	900 mm	1300 mm	2000 mm
weight	0.8 Kg	1.1 Kg	1.9 Kg	2.4 Kg	4.8 Kg
hardness of the plate	1 (extra soft)	1 (extra soft)	2 (soft)	3 (hard)	4 (extra hard)

USAGE

Sanding flat and curved surfaces by velcro system.

PACKAGING

Carton

MANUFACTURER

INNOVIA, s.r.o.
Sterboholska 1421/37
102 00 Prague, Czech Republic

Tel: **+420 725 929 393**
info@flexisander.com
www.flexisander.com

FLEXISANDER
ahead of the curve

The manufacturer reserves the right to make changes to products.
Current information is available at www.flexisander.com. Made in Czech Republic (EU).

X FSB 056111



X FSB 084112



X FSB 112113



X FSB 196114





OWNER'S MANUAL



FSB 042071
FSB 056111
FSB 084112
FSB 112113
FSB 196114

CAUTION!

Before operating the device, carefully read this manual and strictly follow the instructions listed below:

- ◆ The dust that arises from sanding is harmful to your health, therefore, always use a respiratory protection mask.
- ◆ Wear sight protection.
- ◆ Never use for sanding any materials containing asbestos.

WORK AREA SAFETY

- ◆ Use abrasive materials recommended by the manufacturer.
- Keep work area clean and well lit. Cluttered or dark areas invite accidents.
- ◆ Keep children and bystanders away while operating a power tool. Distractions can cause you to lose control.
- Do not overreach. Keep proper footing and balance at all times. This enables better control of the tool in unexpected situations.
- Dress properly. Do not wear loose clothing or jewellery. Keep your hair, clothing and gloves away from moving parts. Loose clothes, jewellery or long hair can be caught in moving parts.
- Provide for good ventilation of the working place.
- It is recommended to wear a dust respirator. Observe the relevant regulations in your country for the materials to be worked.
- ◆ Prevent dust accumulation at the workplace. Dusts can easily ignite.

ABRASIVES MOUNTING

The machine is equipped with a flexible Velcro system insole for easy and quick attachment of the sanding material.

- Before use, check the Velcro on planchette is not mechanically damaged (e.g. melted due to excessive use, etc.)
- Attach dimensionally the same sheet of sanding material so that the holes for dust extraction sanding sheet are flush with the holes on the planchette.
- ◆ Remove the sanding sheets by lightly pulling its edges.

RECYCLING

Equipment and its accessories and packaging surrender after the end of its useful life to a collection point for re-processing.





OWNER'S MANUAL

WARRANTY

We provide guarantee on material and manufacturing defects hidden under the legal provisions of the given country, at the minimum at least 12 months. In the EU, the warranty period is 24 months for exclusively private use (please see invoice or delivery note for further information). Damage resulting from usual wear and tear, overloading, mis-use and improper use and handling, respectively damage caused by the user or use contrary to the instruction manual, or damage that has been known to a buyer before purchasing the product, are excluded from the guarantee. Any complaints can only be accepted if the machine is complete, not dismantled, sent back to the manufacturer or authorised service centres (please see list of service centres). Keep the operating instructions, safety instructions and proof of purchase. Otherwise the manufacturer operates in accordance to its issued warranty conditions in latest update.